

**200A, 15 kV, 25kV & 35kV
Grounding Elbow**



APPLICATION

The Chardon Grounding Elbow provides a circuit between energized and nonenergized sections of the distribution line. The Grounding Elbow can be assembled on the loadbreak bushing insert, feed thru Insert or junction of a pad-mounted transformer or other apparatus.

The Chardon Grounding Elbow is molded with high quality yellow EPDM insulating rubber and features a copper connector and tin-plated copper probe. Each grounding elbow comes with a standard 6' (190cm) 1/0, 600V copper grounding cable.

Cables, transformers, and switchgear can be visibly grounded using the 15, 25 & 35 kV

Grounding Elbows on their own or combined with a feed-through of the same voltage and current rating.

The Grounding Elbows are designed to mate with 200A loadbreak bushings and accessories conforming to IEEE Std 386™ standard (rated 8.3/14.4 kV for 15 kV Grounding Elbows, 15.2/26.3 kV for 25 kV Grounding Elbows, and 21.1/36.6 kV for 35 kV Grounding Elbows).

ORDERING INFORMATION


Each 15kV, 25kV and 35kV Ground Elbow kit includes the following:

- / Grounding Elbow Kit
(Grounding Elbow, 6' (190 cm) 1/0 Yellow Cable Crimped with Lug, Probe)
- / Silicone Grease
- / Installation Instruction Sheet
- / Clamp Kit (Optional)

To order a Chardon 15kV, 25kV or 35 kV Grounding Elbow kit, follow the steps below:

| | |
|----------------------------------|-------------|
| 15 kV Grounding Elbow | 15-GLE200 |
| 25 kV Grounding Elbow | 25-GLE200 |
| 35 kV Grounding Elbow | 35-GLE200 |
| 15kV Grounding Elbow + Clamp Kit | 15-GLE200CK |
| 25kV Grounding Elbow + Clamp Kit | 25-GLE200CK |
| 35kV Grounding Elbow + Clamp Kit | 35-GLE200CK |

DETAILED COMPOSITION OF GROUNDING ELBOW



• 15/25/35-GLE200-081122-REV01

CHARDON GROUNDING ELBOW CLAMP





CHARDON TAIWAN CORPORATION

No.37 Min-Chie Road, Tung Lo
Industrial Park, Miao Li, Taiwan 366

Tel : +886-37-984385

Fax : +886-37-984770

www.chardongroup.com • info@chardongroup.com